

100V-240V AC



Approval Marks



Certified

EN 61347-1:2008
EN 61347-2-13:2006
EN 62384:2006

Electronic

Parameter	Conditions	Min	Nom	Max	Unit
I/P Voltage Range		90	100-240	264	Vac
Input Frequency		47	50-60	63	Hz
Output Power (Pout)	Regular LED	0	-	3	W
Input Current (Iin)	25°C, Nominal Input@230VAC	-	40	-	mA
Output Voltage(Vout)		22.8	24	25.2	Vdc
Output Current (Iout)	25°C, Nominal Input	-	-	125	mA
Power Factor	Full Load	-	0.40	-	
Protection	Overload Protection				
	Short Circuit Protection				
	Over Heat Protection				
Ambient Temp.		-20	-	+50	°C
Case Temp. (Tc)	Normal Conditions	-	-	+70	°C


Lamp Type Regular LED 0.04~0.1W

Application Space

Indoor Use
(Low Humidity, No Condensation)

Physical

Parameter



L : 55.8 mm H : 20 mm
M : 50 mm K : 3 mm
N : 21.8 mm R : 2 mm
W : 39 mm
Slot On One Side Allowing Alignment : M+/-3 mm
Tolerance : ≥0 ~ 100 ≥ +/-0.5mm
100 ≥ +/-1 mm
Terminal Block : PRI : Screw Type
SEC : Screw Type
Housing Material : Polycarbonate
Soldering : Lead-Free, Comply With RoHS
Label : Surface Print

Wiring Diagram

